



# 75" Android Based Interactive Flat Panel Displays

Resolution: 3840x2160 (UHD)

Brightness: 400 cd/m²

Touch Points: 10 Points Multi Touch

. Touch Techology: IR Touch

Interface: HDMI 2.0 / VGA / USB /RS232 / RJ45 / RJ12 for sensors / IR /HP / Audio / Speaker

## **Key Features**



#### Palm Erase

Automatic palm erasing function allows teachers and students to simplify the white board experience with smooth writing and erasing.



#### **Wireless Presentation**

Teachers, students or any user can share their screen efficiently and conveniently in the classroom or meeting room via EShare application. This application can connect any operating system and show up to 4 different screen at the same time.



## Ease of use with Android

Android gives teachers one touch access for lessons and collaboration tools including whiteboard, web browser, apps library, and native wireless screen sharing.



#### **Different Sizes for various classrooms**

Available in a variety of large screen sizes, the IFD range gives customers the options to choose exactly what they need for their room size.



### PANEL

Screen Size 75" Panel Technology IPS

Backlight Type Direct-Type LED Brightness (typical) 400 cd/m<sup>2</sup>

Native Resolution 3840 x 2160 (16:9) - UHD

Contrast Ratio (typical) 1200:1

Dynamic Constrast Ratio 40000:1

Panel Life Time ( Min. ) 30.000 Hrs

Response Time (typical) 8 ms

Active Area (H x V) 1650 x 928 mm

Pixel Pitch (H x V) 0.429 x 0.429 mm

PPI (pixel per inch) 59

Viewing Angle 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10

Color Value 1.07 B (10-bit)

Screen Treatment 2H
Haze Level 3%
Refresh Rate 60 Hz
Front Type Touch Bezel
Orientation Horizontal
Operation Hours 16/7 Panel
Area of Usage Indoor

### MAINBOARD

fainboard Model 17MB135VS

## MONITOR CONNECTIVITY

RGB Input VGA(DE-15F) RGB Output N/A

Video Input 3xHDMI2.0, 2xUSB2.0, USB2.0(Internal), 1xMicroSD

Video Output HDMI2.0 Audio Input Line In L/R

Audio Output Headphone, Optic SPDIF

External Control RS232(DE-9F), 2\*Ethernet(RJ45), Service(RJ12)

External Sensor RJ12

## TOUCH TECHNOLOGY

Type of Touch Technology Infrared (IR) Technology

Supported Point 10 Points

Sensitivity Any touch with finger, gloved hand or pointer

Connectivity HID, TUIO, Flash

Supported OS and HID, TUIO, Flash Windows 7, Windows 8, Windows 8

Applications 10, Vista, XP, Mac OS, Linux, Android

Orientation Landscape support
Calibration No need
Accuracy 90%

Reporting Rate up to 450 fps

Glass Type Anti Glared (AG), Tempered 4mm

Frame Rate up to 450 fps
Communication USB2.0
Power Supply Mode USB
Supply Voltage DC 5V +/- 5%

Average Current Response Time

Touch Accuracy +/-2mm (over 90% area)

Object Sizes for Touch 5 mm
Touch Durability Unlimited
HID Compatibility YES USB

## MECHANICAL

Product Dimensions (WxDxH)  $1731 \times 119 \times 1008 \text{ mm}$  Package Dimensions (WxDxH)  $1948 \times 310 \times 1248 \text{ mm}$ 

Product Weight 58.3 kg
Package Weight 72.4 kg
Vesa Mounting 600 x 400

 $\begin{array}{ccc} \mbox{Vesa Mounting} & \mbox{600 x 400 mm - M6} \\ \mbox{Bezel Width} & \mbox{B:38 | T:38 | L/R:38 mm} \end{array}$ 

#### POWER

Power Supply 110 VAC - 240 VAC - 50/60 Hz

## FEATURES

Main Features Android 7.1 OS, Open Content Management Support, Scheduler, USB-

Autoplay, Auto-Launch, HDMI-CEC, HDMI-Hotplug, Auto-switch on Failover, Panel Lock, OSD Rotation, NoSignalPowerOff, Screen Saver, Pixel shift, Scheduler, Videowall support, remote control via LAN,

Real Time Cloc

Mechanical Joystick, IR Extender Support, Rocker Switch, Detachable power cable, Carrying slots, Detachable logo positioning, Cable Holder

Optional Features OPS Compliance Speaker 2 x 12 W

## **ENVIRONMENTAL CONDITIONS**

Operating Temperature 0-40°C Operating Humidity 10-90%

#### POWER CONSUMPTION

Off ≤ 0.5W

#### **ACCESSORY**

Standard QSG, IB, Power Cord, Remote Control Unit, RC Battery, Mounting Kit,

Extension Brackets, IR Extender Cable

# CERTIFICATION Safety YES EMC YES

YES

CE

